

WHAT IS CLAIMED IS:

505 a27 1. A display system comprising:
a host apparatus having an image output interface;
a display apparatus which is operated by supply of a
video signal and power from said host apparatus; and
a communication function for receiving and transmitting
data between said host apparatus and said display apparatus,
wherein said host apparatus comprises a storing unit
for storing power consumption data thereof, and
said display apparatus transmits said power consumption
data thereof stored in said storing unit to said host
apparatus to said host apparatus and said host apparatus
processes said received power consumption data, thereby
performing power control of said display system comprising
said host apparatus and said display apparatus.

505 a27 2. A system according to Claim 1, wherein an interface
specification for communicating said power consumption data
conforms with a DDC1/DDC2B/DDC2AB standard prescribed by
Video Electronics Standards Association or an expansion
function thereof.

505 a27 3. A system according to Claim 1, wherein said display
apparatus has a mode for operating only said function for

communication with said host apparatus.

505 a 27 4. A system according to Claim 1, wherein said display apparatus further comprises an alarm indicator lamp for alarm display.

505 a 27 5. A display system comprising:
a host apparatus having an image output interface;
a display apparatus which is operated by supply of at least one of a video signal and power from said host apparatus; and

a communication function for receiving and transmitting data between said host apparatus and said display apparatus, wherein said display apparatus comprises a storing unit for storing power consumption data thereof and display-side communication means for transmitting said power consumption data stored in said storing unit, and

said host apparatus comprises host-side communication means for receiving said power consumption data transmitted from said display apparatus and power control means for entirely performing power control of said display system based on said power consumption data received from said host-side communication means.

505 a 27 6. A system according to Claim 5, wherein said display

apparatus further comprises storing means for storing on-screen display information and said display-side communication means transmits said on-screen display information, and

in said host apparatus, said host-side communication means receives said on-screen display information and further comprises information superimposing means for superimposing said received on-screen display information to the video signal.

505A21 7. A display system comprising:

a host apparatus having an image output interface;

a display apparatus which is operated by receiving at least a video signal from said host apparatus; and

a communication function for receiving and transmitting data between said host apparatus and said display apparatus, and

wherein said display apparatus comprises storing means for storing on-screen display information and display-side communication means for transmitting data which is stored in said storing means,

said host apparatus comprises host-side communication means for receiving the on-screen display information transmitted by said display apparatus and information superimposing means for superimposing the on-screen display

000453-0294
104220-229460

information received from said host-side communication means to the video signal, and

in said display system, said host-side communication means transmits the video signal superimposed to the on-screen display information and said display-side communication means receives the transmitted signal, thus, said display apparatus displays an image of said on-screen display information.

sub a27 8. A system according to Claim 5, wherein said display apparatus has an interface specification for communication between said host-side communication means and said display-side communication means which conforms with a DDC1/DDC2B/DDC2AB standard prescribed by Video Electronics Standards Association or an expansion function thereof.

sub a27 9. A system according to Claim 7, wherein said display apparatus has an interface specification for communication between said host-side communication means and said display-side communication means which conforms with a DDC1/DDC2B/DDC2AB standard prescribed by Video Electronics Standards Association or an expansion function thereof.

sub a27 10. A system according to Claim 5, wherein said display apparatus includes a mode for operating only said

function for communication with said host apparatus.

505a27 11. A system according to Claim 7, wherein said display apparatus includes a mode for operating only said function for communication with said host apparatus.

12. A system according to Claim 5, wherein said display apparatus further comprises an indicator lamp for alarm display.

13. A system according to Claim 7, wherein said display apparatus further comprises an indicator lamp for alarm display.

505a37 14. A system according to Claim 6, wherein said host apparatus further comprises first storing means for storing the on-screen display information thereof and second storing means for storing the on-screen display information of said display apparatus which is received via said host-side communication means, and

said information superimposing means converts the on-screen display information stored in at least one of said first storing means and said second storing means into indicatable bit map information and superimposes it to the video signal.

101220 237600

505 a37 15. A system according to Claim 7, wherein said host apparatus further comprises first storing means for storing the on-screen display information thereof and second storing means for storing the on-screen display information of said display apparatus which is received via said host-side communication means, and

said information superimposing means converts the on-screen display information stored in at least one of said first storing means and said second storing means into indicatable bit map information and superimposes it to the video signal.

505 a37 16. A system according to Claim 6, wherein said on-screen display information is ASCII text data.

505 a37 17. A system according to Claim 7, wherein said on-screen display information is ASCII text data.

505 a37 18. A system according to Claim 6, wherein said display apparatus can be selectively connected to a plurality of types of host apparatuses.

505 a37 19. A system according to Claim 7, wherein said display apparatus can be selectively connected to a

plurality of types of host apparatuses.

505a37 20. A system according to Claim 6, wherein said host apparatus can be selectively connected to a plurality of types of display apparatuses.

505a37 21. A system according to Claim 7, wherein said host apparatus can be selectively connected to a plurality of types of display apparatuses.

505a37 22. A microdisplay apparatus connected to a host apparatus, comprising:

memory means for storing monitor request voltage information and monitor current consumption information as specific EDID information on said microdisplay apparatus; and

communication interface means for communication with said host apparatus so as to transmit said monitor request voltage information and said monitor current consumption information to said host apparatus.

505a37 23. A display system having a host apparatus and a microdisplay apparatus according to Claim 22, said host apparatus being connected to said microdisplay apparatus via a digital interface, wherein said microdisplay apparatus

further comprises detecting means for detecting a power voltage and a power current consumption, and transmits values of said power voltage and said power current consumption detected by said detecting means to said host apparatus via said communication interface means, and

said host apparatus comprises control means for controlling an output voltage of said host apparatus based on said EDID information obtained when being connected to said microdisplay apparatus and said detected values of the power voltage and power current consumption.

202502231600